


NOTICE OF PROPRIETARY RIGHTS:THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO Somefly technology Co.,Ltd.
IT MUST NOT BE REPRODUCED OR DISCLOSED TO OTHERS OR USED IN ANY OTHER WAY, IN WHOLE OR PART EXCEPT AS AUTHORIZED
IN WRITING BY Somefly technology Co.,Ltd.

RoHS compliant

SYM	REVISION	DESCRIPTION	DFTM	DATE	APPD	APPD



NOTES:
1.MATERIALS AND FINISHES:
BODY – STAINLESS STEEL, PASSIVATED
OUTER CONTACT – STAINLESS STEEL, PASSIVATED
INNER CONTACT – BERYLLIUM COPPER, GOLD PLATING
INSULATOR – PEI
2. ELECTRICAL:
A. IMPEDANCE: 50 OHM
B. FREQUENCY RANGE: DC – 40 GHz
C. VSWR: 1.25 MAX.
D. INSERTION LOSS: 0.05XSQRT[F(GHz)] dB MAX.
E. VOLTAGE RATING: 500 VRMS
F. DIELECTRIC WITHSTANDING VOLTAGE: 1000 VRMS MIN.
G. INSULATION RESISTANCE: 1000 MΩ MIN.

3. MECHANICAL:
A. DURABILITY: 1000 CYCLES MIN.
B. TEMPERATURE RANGE: -40°C TO +125°C
C. COMPATIBLE WITH ALL STANDARD:IEC61169-35

CUSTOMER OUTLINE DRAWING
ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

MATL:		UNLESS OTHERWISE SPECIFIED			DFTM: 006		Somefly technology Co.,Ltd			
		ALL DIMENSIONS ARE IN mm MACHINED SURFACES FINISH 1.6RMS MAX. REMOVE ALL BURRS 0.15×45°MAX. BREAK MACHINE CORNERS 0.15×45°D MAX. FILLET R. TOLERANCES ON DECIMALS .X ±0.2 .XX ±0.1 ANGLES±2° FRACTIONS±N/A			DATE: 2022.05.19					
					CHKD HeTong		2.92 Male Thread-In Waveguide Probe			
					DATE: 2022.05.19					
USED ON:					APPD: Stone					
SCALE: 4/1	DWG SIZE A4	DO NOT SCALE DRAWING		SURFACE (mm ²) XX	WEIGHT (g) XX	DATE: 2022.05.19	SHT	016-K1L06-CS	REV	A.0