

P/N: 003-BA3H01-1S




Interface Standards: IEC61169-33



Technical data

Electrical data	
Impedance	50 Ω
Frequency range	26.5GHz
VSWR	1.35:1
Insertion Loss	0.08√f(GHz)dB
Operating Voltage (AC)	250
DWV(AC)	1000
Shielding Effectiveness (dB)	≥-90dB
Insulation Resistance	5000MΩ
Mechanical data	
Coupling nut torque Recommended	/
Durability (mating)	1000Min
Size	Length: 1.045 in (25.3) Width (Dia): 0.314 in (7.99mm)
Weight	0.018lbs (8.3g)
Environmental data	
Temperature range	-65 to +165 °C
RoHS	Compliant
Shock	MIL-STD-202, Method 213, Test Condition I
Vibration	MIL-STD-202, Method 204, Test Condition D -
Salt Spray	MIL-STD-202, Method 101, Test Condition B, Solution 5%
Material and plating	
Centre contact	Beryllium Copper, Gold Plating
Out contact	Beryllium Copper, Gold Plating
Body	Stainless Steel, Gold Plating
Insulator	PTFE

Mechanical Outline



ASSEMBLY PROCEDURES

1. STRIP CABLE AS SHOWN IN (A). DO NOT NICK INNER CONDUCTOR.
2. PRE-TIN CABLE JACKET TO APPROXIMATE DIMENSION AS SHOWN IN (A).
3. INSERT CABLE THRU ADAPTER UNTIL IT BOTTOMS . SOLDER